

## WF2710



- >802.11AC standard of next generation Wi-Fi technology
- >Workes seamlessly with all 802.11a/b/g/n/ac devices
- >2.4GHz 300Mbps & 5GHz 433Mbps simultaneous dual band
- >3 \* 5dBi high gain antennas for powerful wireless coverage
- >Multiple SSID providing up to 6 additional wireless networks for visitors
- >Easy wireless security setup at a push of WPS button
- >Quick setup, with built-in multilingual web management page

The netis router WF2710 equipped with the next generation 802.11AC Wi-Fi technology, will offer you simultaneous dual band connection with 433Mbps wireless speeds over the crystal clear 5GHz band and 300Mbps over the 2.4GHz band, ideal for faster downloading, online gaming, internet calling and HD video streaming

## AC750 Wireless Dual Band Router

## WF2710

| Wireless              |  |   |  |
|-----------------------|--|---|--|
| Standards             | IEEE 802.11b/g/n 2.4GHz; IEEE 802.11a/n/ac 5GHz  |   |  |
| Signal Rate           | Up to 300Mbps 2.4GHz; Up to 433Mbps 5GHz   |   |  |
| Frequency Range       | 2.4-2.4835GHz;   | 5.180-5.825GHz  |  |
| Transmit Power        | 20dBm (MAX)  |   |  |
| Data Transfer Rate    | 802.11ac: 80MHz(433Mbps)   |   |  |
|                       | 802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps);   |   |  |
|                       | 20MHz (144Mbps, 130Mbps, 115Mbps, 89Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense) |   |  |
|                       | 802.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps)        |   |  |
|                       | 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)                                 |   |  |
| Wireless Mode         | AP, WDS, AP+WDS, Repeater, Client, Multiple AP   |   |  |
| Wireless Security     | 64/128-bit WEP<br>SSID Broadcast Enable/Disable  | WPA-PSK/WPA2-PSK (TKIP/AES)<br>Wireless MAC Filtering                               |  |
| Hardware              |  |   |  |
| Standard              | IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX  |   |  |
| Interface             | 1 * 10/100M Auto MDI/MDIX RJ45 WAN port;   |   | 4 * 10/100M Auto MDI/MDIX RJ45 LAN port                                    |
| LED                   | PWR, WPS, SYS, 2.4G, 5G, LAN1-4, WAN, WPS  |   |  |
| Button                | Default, WPS   |   |  |
| Antenna               | 4 * external 5dBi antennas, omni-directional   |   |  |
| Power Supply          | DC 12V/1A (Output)   |   |  |
| Dimensions(L x W x H) | 145 x 55 x 41 mm   |   |  |
| Weight                | 151g   |   |  |
| Software              |  |   |  |
| WAN Type              | DHCP, Static IP, PPPoE, L2TP, PPTP, Dual Access, WiSP                                  |   |  |
| Port Forwarding       | Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port                          |   |  |
| QoS                   | WMM, Bandwidth Control   |   |  |
| Access Control        | IP/MAC/Domain Filtering  |   |  |
| VPN Pass-through      | PPTP, L2TP, IPSEC  |   |  |
| Others                | DDNS, Static Routing, WOL, Remote Management, Firmware upgrade, Backup & Restore       |   |  |
| Others                |  |   |  |
| Certification         | FCC, CE, KC  |   |  |
| Environment           | Operating Temperature: 0°C~40°C<br>Operating Humidity: 10%~90% non-condensing          |   | Storage Temperature: -40°C~70°C<br>Storage Humidity: 5%~90% non-condensing |
|                       | Package  | 1 * WF2710 1 * 12V/1A Power Adapter 1 * Ethernet Cable 1 * Quick Installation Guide |  |

### Topological Graph:

